

Leistungserklärung

Silikon FO


LE/DoP-Nr. DC7001

- 1. Kenncode des Produkttyps:** Silikon FO
- 2. Ident-Nr.:** Chargennummer siehe Produktverpackung
- 3. Verwendungszweck:**
1 Komponenten Silikondichtstoff für die folgenden Anwendungen:
- Fassadenanwendung TYP 25LM extern/intern CC gemäß EN 15651-1
 - Verglasung TYP 25LM CC gemäß EN 15651-2
 - Sanitärbereich TYP XS1 gemäß EN 15651-3
 - Bodenfugen TYP 25LM CC extern/intern gemäß EN 15651-4
- Träger: Glas/Glas/Glas/Glas+M1
Konditionierung: A
- 4. Hersteller:** WS INSEBO GmbH
Industriestraße 24
A-2325 Himberg bei Wien
- 5. System der Bewertung der Leistungsbeständigkeit:** 3
- 6. Harmonisierte Norm:** EN 15651
- 7. Notifizierte Stelle:** ITC Zlin NB-Nr. 1023 hat als notifizierte Prüflabor im System 3 die Erstprüfung durchgeführt und die Prüf- und Klassifizierungsberichte erstellt
- 8. Wesentliche Merkmale:** siehe Tabellen auf den Folgeseiten

Die Leistung des Produkts gem. Nummer 1 und 2 entspricht der erklärten Leistung nach Nummer 8. Verantwortlich für die Erstellung der Leistungserklärung ist der Hersteller gemäß Nummer 4.

Unterzeichnet für den Hersteller und im Namen des Herstellers von:

Himberg bei Wien, den 06.09.2021



.....
ppa. Dipl.-Ing. (FH) Thomas Koternetz, MSc
kaufm. und produkttechnischer Leiter



.....
DI Dr. Michael Haberkorn
Produktmanager

EN 15651-1: Klasse des Dichtstoffes für Fassadenelemente

Eigenschaften	Klasse des Dichtstoffes für Fassadenelemente 25LM F-EXT-INT-CC	Prüf- verfahren
Rückstellvermögen	≥70 %	EN ISO 7389
Standvermögen	≤ 3 mm	Siehe 4.3.3
Dehnspannungswert (MPa)	≤0,4 (23 °C) und ≤0,6 (-20 °C)	EN ISO 8339
Bruchdehnung (%)	-	EN ISO 8339
Zugverhalten unter Vorspannung	NF	EN ISO 8340
Haft-/Dehnverhalten bei unterschiedlichen Temperaturen	NF	EN ISO 9047
Haft-/Dehnverhalten unter Vorspannung nach dem Eintauchen in Wasser	NF	EN ISO 10590
Volumenverlust (%)	≤10	EN ISO 10563
Haft-/Dehnverhalten bei konstanter Temperatur	-	EN ISO 9046
Haft-/Dehnverhalten nach dem Eintauchen in Wasser: Dehnung (%) bei 23 °C	-	EN ISO 10591

NF = Kein Versagen (en: No Failure) nach EN ISO 11600.

Produkteigenschaften gemäß EN 15651-1 ZA.1.1

Verwendungszweck: Fugendichtstoff für Außenanwendungen	
Wesentliche Eigenschaften	Wert
Brandverhalten	E
Freisetzung von umwelt- und / oder gesundheitsgefährdenden Chemikalien	Siehe Sicherheitsdatenblatt
Wasser- und Luftdichtheit	
Standvermögen	≤ 3 mm
Volumenverlust	≤10
Zugverhalten (d. h. Dehnverhalten) nach dem Eintauchen in Wasser (bei 23 °C)	-
Zugverhalten (d. h. Dehnverhalten) unter Vorspannung nach Eintauchen in Wasser	NF
Zugverhalten (d. h. Sekantenmodul) für Fugendichtstoffe mit niedrigem Modul, die in kalten Klimazonen (-30 °C) eingesetzt werden ^b	≤ 0,9 MPa
e) Zugverhalten (d. h. unter Vorspannung) für nicht tragende Fugendichtstoffe, die in kalten Klimazonen (-30 °C) eingesetzt werden ^b	
Dauerhaftigkeit	NF

^b Zusätzliche Anforderungen für nicht tragende Dichtstoffe, die für Fugen in kalten Klimazonen vorgesehen sind.

EN 15651-2: Klasse des Dichtstoffes für Verglasungen

Eigenschaften	Klasse des Dichtstoffs für Verglasungselemente 25LM G-CC	Prüf- verfahren
Rückstellvermögen (%)	≥60 %	EN ISO 7389
Standvermögen (mm)	≤ 3 mm	4.3.3
Dehnspannungswert (MPa)	≤0,4 (23 °C) und ≤0,6 (-20 °C)	EN ISO 8339
Haft-/Dehnverhalten unter Vorspannung	NF	EN ISO 8340
Haft-/Dehnverhalten bei unterschiedlichen Temperaturen	NF	EN ISO 9047
Haft-/Dehnverhalten unter Vorspannung nach dem Eintauchen in Wasser	NF	EN ISO 10590
Volumenverlust (%)	≤10	EN ISO 10563
Haft-/Dehnverhalten nach Beanspruchung durch Hitze, Wasser und künstliches Licht	NF	EN ISO 11431
Druckwiderstand	>80N	EN ISO 11432
NF = Kein Versagen (en: <i>No Failure</i>) nach EN ISO 11600.		

Produkteigenschaften gemäß EN 15651-2 ZA.1.1

Verwendungszweck: Fugendichtstoffe für Verglasungen (wie im Anwendungsbereich beschrieben)	
Wesentliche Eigenschaften	Klassen und/oder Schwellenwerte
Brandverhalten	E
Freisetzung von umwelt- und / oder gesundheitsgefährdenden Chemikalien	Siehe Sicherheitsdatenblatt
Wasser- und Luftdichtheit	
a) Volumenverlust	≤10
b) Standvermögen	≤ 3 mm
c) Haft-/Dehnverhalten nach Einwirkung von Wärme, Wasser und künstlichem Licht	NF
d) Rückstellvermögen	≥60 %
e) Zugverhalten (d. h. Sekantenmodul) für Fugendichtstoffe mit niedrigem Modul, die in kalten Klimazonen (-30 °C) eingesetzt werden ^b	≤ 0,9 MPa
f) Zugverhalten (d. h. unter Vorspannung) für Fugendichtstoffe, die in kalten Klimazonen (-30 °C) eingesetzt werden ^b	-
Dauerhaftigkeit	NF
^b Zusätzliche Anforderungen für nicht tragende Dichtstoffe, die für Fugen in kalten Klimazonen vorgesehen sind.	

EN 15651-3: Klasse des Dichtstoffes für den Sanitärbereich

Eigenschaften	Klasse des Dichtstoffes im Sanitärbereich XS1	Prüf- verfahren
Zugverhalten unter Vorspannung	NF	EN ISO 8340
Haft-/Dehnverhalten bei unterschiedlichen Temperaturen	NF	EN ISO 9047
Haft-/Dehnverhalten unter Vorspannung nach dem Eintauchen in Wasser	NF	EN ISO 10590
Haft-/Dehnverhalten nach dem Eintauchen in Wasser: Bruchdehnung (%)	-	EN ISO 10591
Volumenverlust (%)	≤20	EN ISO 10563
Standvermögen (mm)	≤ 3 mm	Siehe 4.3.2.
Mikroorganismen: Wachstumsintensität	0	Siehe 4.3.3.

NF = Kein Versagen (en: *No Failure*) nach EN ISO 11600:2003.

Produkteigenschaften gemäß EN 15651-3 ZA.1.1

Verwendungszweck: Fugendichtstoffe für nicht tragende Anwendungen im Sanitärbereich	
Wesentliche Eigenschaften	Wert
Brandverhalten	E
Freisetzung von umwelt- und / oder gesundheitsgefährdenden Chemikalien	Siehe Sicherheitsdatenblatt
Wasser- und Luftdichtheit	
Standvermögen	≤ 3 mm
Volumenverlust	≤20
Zugverhalten (d. h. Dehnverhalten) - nach dem Eintauchen in Wasser (bei 23 °C), (Klasse S)	-
Zugverhalten (d. h. Dehnverhalten) - unter Vorspannung nach Eintauchen in Wasser (Klasse XS)	NF
Mikrobiologisches Wachstum	0
Dauerhaftigkeit	NF

EN 15651-4: Klasse des Dichtstoffes für Fußgängerwege

Eigenschaften	Klasse des Dichtstoffes für Fußgängerwege 25LM PW-EXT-INT-CC	Prüf- verfahren
Elastisches Rückstellvermögen (%)	≥70 %	EN ISO 7389
Zugverhalten: Sekantenmodul bei (23 ± 2) °C (MPa) bei (-20 ± 2) °C (MPa)	≤0,4 (23 °C) und ≤0,6 (-20 °C)	EN ISO 8339
Zugverhalten unter Vorspannung ^a	NF	EN ISO 8340
Haft-/Dehnverhalten bei unterschiedlichen Temperaturen	NF	EN ISO 9047
Haft-/Dehnverhalten unter Vorspannung nach dem Eintauchen in Wasser	NF	EN ISO 10590
Haft-/Dehnverhalten unter Vorspannung nach dem Eintauchen in Wasser und Salzwasser (jeweils 28 Tage)	NF	EN ISO 10590 modifiziert
Volumenverlust bei nicht absackenden Fugendichtstoffen (%)	≤10	EN ISO 10563
Standvermögen bei nicht ab-sackenden Fugendichtstoffen (mm)	≤ 3 mm	EN ISO 7390
Reißfestigkeit	NF	EN ISO 8340 modifiziert


NF = Kein Versagen (en: *No Failure*).

Produkteigenschaften gemäß EN 15651-4 ZA.1.1

Verwendungszweck: Dichtstoffe für nicht tragende Fugen in Böden	
Wesentliche Eigenschaften	Klassen und/oder Schwellenwerte
Brandverhalten	E
Freisetzung von umwelt- und/oder gesundheitsgefährdenden Chemikalien	Siehe Sicherheitsdatenblatt
Wasser- und Luftdichtheit	
a) Zugverhalten unter Vorspannung	NF
b) Volumenverlust	≤10
c) Reißfestigkeit	NF
d) Haft-/Dehnverhalten unter Vorspannung nach 28-tägiger Wasserlagerung ^a	NF
e) Haft-/Dehnverhalten unter Vorspannung nach 28-tägiger Lagerung in Salzwasser	NF
f) Zugverhalten (h. h. Sekantenmodul) bei (-30 ± 2) °C für kalte Klimazonen ^b	≤ 0,9 MPa
g) Zugverhalten unter Vorspannung bei (-30 ± 2) °C für kalte Klimazonen ^b	NF
Dauerhaftigkeit	NF

^b Zusätzliche Anforderungen für nicht tragende Dichtstoffe, die für Fugen in kalten Klimazonen vorgesehen sind.

Kennzeichnung auf der Verpackung

 1023
14
WS INSEBO GmbH Industriestraße 24 A-2325 Himberg bei Wien
EN 15651-1: 25LM F-EXT-INT-CC EN 15651-2: 25LM G-CC EN 15651-3: XS1 EN 15651-4: 25LM PW-EXT-INT-CC
Details siehe DoP DC7001

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2022

Version 3

Revision: 30.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: INSEBO Silikon FO, all colours

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture Spacings sealent

1.3 Details of the supplier of the safety data sheet

WS INSEBO GmbH

Industriestraße 24, A-2325 Himberg bei Wien

Tel.: +43 (0) 2235/86227-0

e-mail: office@insebo.com

1.4 Emergency telephone number Call local emergency information.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 void

Hazard pictograms void

Signal word void

Hazard statements void

Precautionary statements

P102 Keep out of reach of children.

Additional information:

EUH208 Contains 2-octyl-2H-isothiazol-3-one, N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

2.3 Other hazards No further relevant information available.

SECTION 3: Composition/information on ingredients

3.2 Mixture

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:		
CAS: 112945-52-5 EC number: 601-216-3	silica, amorphous, fumed substance with a Community workplace exposure limit	2.5 - 10%
CAS: 37859-55-5 ELINCS: 484-460-1 Reg.No.: 01-2120004323-76	O,O',O''-(methylsilylidine)trioxime 2-pentanone Acute Tox. 4, H302; Eye Irrit. 2, H319	< 5%

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2022

Revision: 30.05.2022

Trade name: INSEBO Silikon FO, all colours

CAS: 1760-24-3 EINECS: 217-164-6 Reg.No.: 01-2119970215-39	N-(3-(trimethoxysilyl)propyl)ethylenediamine Eye Dam. 1, H318; Skin Sens. 1, H317	< 1%
CAS: 26530-20-1 EINECS: 247-761-7 Index number: 613-112-00-5	2-octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	< 1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: In case of accident or if you feel unwell seek medical advice (show label where possible).

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothes. Rinse skin thoroughly with water and soap. In case of irritation seek medical treatment.

After eye contact:

Rinse opened eye for several minutes under running water. Get medical advice if irritation persists.

After swallowing:

Rinse out mouth with plenty of water. If symptoms of indisposition persist, seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

No special measures are required, use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of harmful gases (e.g. carbon oxides, COx) is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Use protective equipment suitable to the situation.

Additional information Collect runoff separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Particular danger of slipping on leaked/spilled product.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2022

Revision: 30.05.2022

Trade name: INSEBO Silikon FO, all colours

6.2 Environmental precautions:

Do not allow to enter sewers, surface or ground water.
Advise water authority in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid or universal binders, sawdust).
Allow to solidify and remove mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid eye and skin contact with the product.
Provide good ventilation/exhaustion at the workplace.
Wash hands before break and at the end of work.

Information about fire - and explosion protection: No further relevant information available.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Store in cool, dry place in tightly closed original containers.
Protected from moisture.

Information about storage in one common storage facility:

Do not store food, beverages and animal feeding stuffs in the storage area.

Further information about storage conditions:

Keep out of the reach of children and domestic animals.
Keep container tightly sealed.

7.3 Specific end use(s) Sealant

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 112945-52-5 silica, amorphous, fumed

MAK (Austria)	Long-term value: 4E mg/m ³ ; (resp. CAS 7631-86-9)
---------------	---------------------------------------------------------------

MAK (Germany)	Long-term value: 4E mg/m ³ ; vgl. Abschn.V
---------------	-------------------------------------------------------

Regulatory information

MAK (Austria): GKV 2020, 156. Verordnung, 09.04.2021, Teil II
MAK (Germany): MAK- und BAT-Liste

8.2 Exposure controls

Appropriate engineering controls Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Avoid unnecessary contact with the product. Do not eat, drink or smoke at workplace.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2022

Revision: 30.05.2022

Trade name: INSEBO Silikon FO, all colours

Remove contaminated clothing and wash carefully before reuse.

Wash hands before break and at the end of work.

Respiratory protection: Not required if room is well-ventilated.

Hand protection Protective gloves recommended.

Material of gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety goggles recommended.

Body protection: Not required if handled properly.

Environmental exposure controls

Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form:	Pasty
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	Not applicable.
Lower and upper explosion limit:	No data available.
Flash point:	No data available
Decomposition temperature:	Not determined.
pH:	Not determined.
Viscosity	
dynamic:	> 50 Pas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient, n-octanol/water:	No data available.
Vapour pressure:	Not determined.
Vapour density:	Not determined.
Density:	≈ 1 g/cm ³

9.2 Other information

Explosive properties:	No data available
Oxidising properties:	No data available.

Information with regard to physical hazard classes

Explosives	void
Flammable gases	void
Aerosols	void
Oxidising gases	void

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2022

Revision: 30.05.2022

Trade name: INSEBO Silikon FO, all colours

Gases under pressure	void
Flammable liquids	void
Flammable solids	void
Self-reactive substances and mixtures	void
Pyrophoric liquids	void
Pyrophoric solids	void
Self-heating substances and mixtures	void
Substances and mixtures, which emit flammable gases in contact with water	void
Oxidising liquids	void
Oxidising solids	void
Organic peroxides	void
Corrosive to metals	void
Desensitised explosives	void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions No hazardous reactions known if used according to specifications.

10.4 Conditions to avoid Keep dry and avoid extreme temperatures and direct sun exposure.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: None under normal conditions of storage and use.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification: There are no product specific data on toxicology available.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Not skin sensitising based on results on similar mixtures tested using bridging principles according to CLP Regulation Art 9 (4).

Tested in accordance with OECD Test guideline 406 "Buehler Test", study S 4793

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2022

Revision: 30.05.2022

Trade name: INSEBO Silikon FO, all colours

11.2 Information on other hazards

Endocrine disrupting properties None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: For the product there are no ecotoxicological data available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Do not dispose waste or remains together with domestic waste, do not empty into sink or toilet, hand over to hazardous waste disposers.

Small quantities of cured residue can be disposed of along with domestic waste according to local regulations.

European waste catalogue

08 04 09: waste adhesives and sealants containing organic solvents or other dangerous substances

Uncleaned packaging

Recommendation:

Cartridges/buckets/pouches should be emptied completely and should preferably be recycled or reused in compliance with the local/national regulations. Cartridges/buckets/pouches not emptied appropriately or remains have to be disposed of like the product.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA void

14.2 UN proper shipping name

ADR, IMDG, IATA void

14.3 Transport hazard class(es)

ADR, IMDG, IATA

Class void

14.4 Packing group

ADR, IMDG, IATA void

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2022

Revision: 30.05.2022

Trade name: INSEBO Silikon FO, all colours

14.5 Environmental hazards:	not applicable
14.6 Special precautions for user	not required
14.7 Maritime transport in bulk according to IMO instruments	not applicable
UN "Model Regulation":	void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations: -

Classification according to VbF: No data available.

Water hazard class: Water hazard class (German Regulation) 1 (self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH071 Corrosive to the respiratory tract.

Further information:

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008: Bridging principle "Substantially similar mixtures".

Date of previous version: 03.03.2022

Abbreviations and acronyms:

CLP: REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CAS: Chemical Abstracts Service (division of the American Chemical Society)
EINECS: European Inventory of Existing Commercial Chemical Substances
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
MAK: maximum concentration of a chemical substance in the workplace
PBT: persistent, bioaccumulative and toxic properties
vPvB: very persistent and very bioaccumulative properties
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
VbF: Ordinance on the storage of combustible liquids, Austria

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2022

Revision: 30.05.2022

Trade name: INSEBO Silikon FO, all colours

Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2
Skin Corr. 1: Skin corrosion/irritation – Category 1
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Data compared to the previous version altered: Section 2.16