



DECLARATION OF PERFORMANCE

N° 410102013-04-10

NOVOVIS

1. Unique identification code of the product-type :

Joint paper tape for gypsum plasterboards

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

Joint paper tape for gypsum plasterboards

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer :

Jointing materials for gypsum plasterboards

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

Société Novovis SAS

140, Rue Louis Blériot, ZAC Marcel Dassault, 34435 St Jean de Védas - France

Tel : (0033) 467.17.90.27 / Fax : (0033) 467.42.21.42 / www.novovis.com

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2) :

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard :

Centre Scientifique et Technique du Bâtiment (CSTB)

performed the dimensional stability and tensile strength test of the joint paper tape

under system 3

and issued Test report n° EEM 06 26003954

8. Declared performance

| Essential characteristics | Performance | Harmonized technical specification |
|---------------------------|-----------------------------------|------------------------------------|
| Reaction to fire | NPD | EN 13963 |
| Flexural strength | NPD | EN 13963 |
| Tensile strength | 5,239 N/mm | EN 13963 |
| Dimensional stability | - 0,1 % (length) et 1,2 % (width) | EN 13963 |

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Déborah FANNIERE
Quality Manager

Le 14/03/2013

Paper joint tape



**MANUFACTURED
ACCORDING
TO NF EN 13963**

Description

Roll of specific kraft paper which has been sanded, microperforated and pre-folded.

Both faces have been sanded so to obtain a better adhesion to the joint compound used.

The tape has been microperforated thanks to an electric device so to make a better smoothing when set up on the joint compound.

Pre-folded on the center so to position the tape easily when needed.

Application

Straight or concave joints between plasterboards (wall partitions and ceilings).

Use instructions

Make sure that the surface to work on is clean (no dust nor grease).

Use a taping knife. Coat the part to joint between two plasterboards with 3 mm of filling compound.

Set up firmly the joint tape. Put off excess of filling compound with the taping knife. Coat on the band set up. Recoat with a finishing joint compound.

Once all dried, sand lightly with a fine abrasive.

Temperature of use: from 5°C to 30°C

Technical features

Composition

Material body: bleached long-fibers paper kraft, treated anti-moisturing.

Dimensions

| | | | |
|-------------------------|-------|-------|-------|
| Width | 51 mm | 51 mm | 51 mm |
| Length | 23 m | 75 m | 150 m |
| Mandrel diameter | 65 mm | 65 mm | 65 mm |

Tests

Resistance to fire: Non determined performance

Flexural strength: Non determined performance

Yield strength resistance: 5,239 N/mm

Dimensional stability:

- Length: - 0,1 %
- Width: 1,2 %

Warehousing recommendations

Dry place with a constant temperature between -10° C and +60° C

ZAC Marcel Dassault
140, Rue Louis Blériot – BP 311
34435 St Jean de Védas – France

Tel : 0033 467 179 060
Fax : 0033 467 422 142
e-mail : contact@novovis.com