

WKRĘT-MET Sp. z o.o. Sp. komandytowa ul. Wincentego Witosa 170/176 Kuźnica Kiedrzyńska 42-233 Mykanów tel. +48 34 3777 100, fax +48 34 328 01 73



DECLARATION OF PERFORMANCE No 3/SK/13

1. Unique identification code of the product-type:

LFNØ10 (ŁFNØ10)

 Type, batch or serial number or any other element allowing identification of the construction product

The batch number is the production date shown on the box as dd/mm/yy

 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer.

Plastic anchor for fixing of external thermal insulation composite systems with rendering in concrete and mansonry

 Name, registered trade name or registered trade mark and contact address of the manufacturer WKRĘT-MET Sp. z o.o., sp. komandytowa ul. Wincentego Witosa 170/176 Kuźnica Kiedrzyńska PL 42-233 Mykanów

 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

 In case of the declaration of performance concerning a construction product covered by a harmonised standard.

not relevant

 In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

ITB - 1488 issued - ETA-06/0105 on the basis of ETAG 014

Notified factory production control certification body No. 1488, ITB performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control 2+ and issued the certificate of conformity of the factory production control (FPC) WE 1488-CPR-0035/Z.

9. Declared performance

| Essential characteristics | conrete C12/15 | concrete C16/20 | solid clay bricks | sand-lime solid bricks | vertically perforated sand-lime bricks | vertically perforated clay bricks | poro- therm | mega- max | Harmonised technical specification |
|--------------------------------------|-------------------|--------------------|-------------------------|---------------------------|----------------------------------------|-----------------------------------------|----------------|--------------|------------------------------------------|
| Charactersitic resistance [kN] | NPD | NPD | 0,60 | NPD | NPD | 0,50 | NPD | NPD | |
| Point of thermal transmittance [W/K] | | NPD | | | | | | | |
| Plate stiffness [kN/mm] | | NPD | | | | | | | |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Kuźnica Kiedrzyńska 1.04.2014 r.

"WKRET-MET"

(signature)

President - Woffriech Klimas

(place and date of issue)