

DECLARATION OF PERFORMANCE No 9/SK/13

1. Unique identification code of the product-type: **LTXØ10 (ŁTXØ10)**
2. Type, batch or serial number or any other element allowing identification of the construction product: **The batch number is the production date shown on the box as dd/mm/yy**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Plastic anchor for fixing of external thermal insulation composite systems with rendering in concrete and masonry**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer: **WKREŃ-MET Sp. z o.o., sp. komandytowa
ul. Wincentego Witosa 170/176
Kuźnica Kiedrzyńska
PL 42-233 Mykanów**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified: **not relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: **not relevant**
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **ITB – 1488 issued – ETA-08/0172
on the basis of ETAG 014
Notified factory production control certification body No. 1488, ITB performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control 2+ and issued the certificate of conformity of the factory production control (FPC) WE 1488-CPR-0035/Z.**
9. Declared performance

Essential characteristics	concrete C12/15	concrete C16/20	solid clay bricks	sand-lime solid bricks	vertically perforated sand-lime bricks	vertically perforated clay bricks	LAC	AAC2	AAC6	Harmonised technical specification
Characterstic resistance [kN]	0,60	0,75	0,60	NPD	NPD	NPD	0,50	NPD	0,30	ETA-08/0172 from 17.06.2013 according to ETAG 014
Point of thermal transmittance [W/K]	0,000									
Plate stiffness [kN/mm]	0,40									

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Kuźnica Kiedrzyńska
1.04.2014 r.

(place and date of issue)

President - Wojciech Klimas

„WKREŃ-MET”
Sp. z o.o., Sp. komandytowa
ul. Wincentego Witosa 170/176
Kuźnica Kiedrzyńska, 42-233 MYKANÓW
NIP 573-030-39-74, IDS 002747648
KRS 0000408340

(signature)